

Delock USB 2.0 to 2 x serial RS-232 adapter

Description

This EASY-USB Type-A to serial adapter by Delock provides two RS-232 DB9 interfaces for printers, measuring instruments, controllers, IoT devices etc.



ca. 60 cm

Specification

- Connectors:
 - 1 x EASY-USB 2.0 Type-A male >
 - 2 x serial RS-232 DB9 male with nuts
- Chipset: ASIX MCS7820
- Databits: 5, 6, 7, 8
- Stop bits: 1, 2
- FIFO: 512 Byte buffer bi-directional
- Parity: even, odd, none, mark, space
- Flow control: none, hardware RTS / CTS, software XON / XOFF
- Signals: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Data transfer rate up to 460.8 Kb/s
- Supports: UHCI / OHCI / EHCI
- Serial connector with nuts
- Supports remote wake-up and power management
- Compatible with 16C450 / 16C550 UART
- 1 x ferrite core
- Length incl. connectors (L): ca. 0.6 m

System requirements

- Linux Kernel 2.6 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- EASY-USB 2.0 to 2 x serial adapter
- Driver CD
- User manual

Item no. 63950


EAN: 4043619639502

Country of origin: China

Package: Retail Box




Images



EASY-USB

PCB with both sided contacts

contacts



General	
Function:	Plug & Play Remote Wake-Up IrDA 115K Baud Custom Baud Enable
Specification:	RS-232 (EIA / TIA) USB 2.0
Supported operating system:	Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit ex Linux Kernel 2.6.x
Interface	
Connector 1:	1 x Easy USB Type-A
Connector 2:	2 x Serial RS-232 DB9 male
Technical characteristics	
Chipset:	ASIX MCS7820
Data transfer rate:	2 x 460.8 Kbps
FIFO:	512 Byte
Data transmission:	asynchronous full duplex
Physical characteristics	
Connector color:	black
Housing material:	Plastic
Cable colour:	black
Cable length incl. connector:	ca. 60 cm
Screw type:	#4-40 UNC